



کولرهای گازی دو تیکه توچال الکتریک



ECO FRIENDLY

-  **Auto-Restart**
راه اندازی مجدد خودکار
-  **Timer**
قابلیت زمانبندی
-  **Sleep Mode**
حالت خواب
-  **Quick Connector**
اتصال سریع
-  **Dual Sides Water Outlet**
قابلیت خروج آب از دو سمت
-  **Self-diagnosis Function**
عیب یابی خودکار

با گاز R410 - دوستدار محیط زیست

◀ ۵ سال ضمانت کمپرسور

◀ ۱۸ ماه گارانتی قطعات فنی

◀ ۱۰ سال خدمات پس از فروش

◀ نصب رایگان

◀ مخصوص آب و هوای گرم و خشک



سیستم های تهویه مطبوع توچال الکتریک (اسپلیت دیواری)

Model		Indoor/Outdoor Capacity		TAI12-R/TAU12-R	TAI18-R/TAU12-R	TAI24-R/TAU12-R
Nameplate Parameter	Rated Capacity (w)		Cooling	3517	5275	7033
	Rated Power Consumption (w)		Cooling	1060	1650	1950
	Rated Running Current (A)		Cooling	4/9	7	8/6
	EER			3.3	3.2	3.6
	Max. Input Power (W)			1600	2200	2800
	Max. Input Current (A)			8	11/5	13
	Power supply source (V/Ph/Hz)			220~240V-1-50Hz	220~240V-1-50Hz	220~240V-1-50Hz
	Refrigerant			R410A	R410A	R410A
	Refrigerant Charged (g)			830	1000	1250
	Max. Discharge Pressure (Mpa)			4/15	4/3	4/15
	Max. Suction Pressure (Mpa)			1/15	1/15	1/15
	Air Flow Volume (m ³ /h)			580	850	1150
	Noise level (dB(A))			43	47	49
	Noise level (dB(A))			53	54	59
	Indoor unit weight (Net) (Kg)			8	12	14/5
Outdoor unit weight (Net) (Kg)			28/5	36	42	
Indoor unit configuration	evaporator	Multi-bend		3	3	3
		Tube	Material	Inner-grooved copper	Inner-grooved copper	Inner-grooved copper
			Material	Hydrophilic aluminium foil	Hydrophilic aluminium foil	Hydrophilic aluminium foil
	Fin	Material	Hydrophilic aluminium foil	Hydrophilic aluminium foil	Hydrophilic aluminium foil	
		Fins per inch	25.4mm	19	17	17
Dimension	Net Dimension (W&D&H) (mm)		750×285×200	900×310×225	1082×330×233	
	Packing Dimension (W&D&H) (mm)		820×347×277	970×382×302	1130×395×300	
Connection	Connect pipe	Material	copper	copper	copper	
		Length	3/5	3/5	3/5	
		Thickness	0/5	0/5	0/5	
		Liquid tube Diameter (mm)	6	6	6	
		Thickness	0/6	0/75	0/75	
		Gas tube Diameter (mm)	9	12	15/88	
Outdoor unit configuration	Compressor Model		ASM125V1VFT	ASL193MV-C7EU	ASH232MV-C7EU1	
	Compressor Parameter	type	ROTARY	ROTARY	ROTARY	
		Brand	GMCC	HIGHLY	HIGHLY	
		Capacity	3610	4695	5580	
		Input	845	1565	1860	
	Fan system	Fan	Type	axial flow fan	axial flow fan	axial flow fan
		condenser	Tube	Material	Inner-grooved copper	Inner-grooved copper
	Dimension		Packing Type		N	N
		Net Dimension (W&D&H) (mm)		730×545×285	800×545×315	825×655×310
		Packing Dimension (W&D&H) (mm)		850×620×370	920×620×400	945×725×435
Packing Dimension (W&D&H) (mm)						

دفتر مرکزی اهواز: ناحیه صنعتی سپیدار، بلوار بعثت، خیابان شادی یک
 دفتر تهران: سهرودی شمالی، خیابان دکتر قندی غربی، پلاک ۸۳، واحد ۴
 نمایشگاه جزیره کیش: جزیره کیش، بلوار ایران، قطعه ایکس ۴۶
 کارخانه: اهواز، شهرک صنعتی شماره سه، فاز دو، نبش خیابان سازندگی

تلفن: ۰۶۱-۳۳۲۷-۸۱۳
 فکس: ۰۶۱-۳۳۲۷-۸۱۳
 تلفن: ۰۲۱-۸۸۵-۲۴۰۰
 فکس: ۰۲۱-۸۸۵-۲۴۹۴
 تلفن: ۰۷۶-۴۴۲۵-۸۵
 فکس: ۰۷۶-۴۴۲۲۸۹
 تلفن: ۰۶۱-۳۳۲۷-۷۱
 فکس: ۰۶۱-۳۳۲۷-۸۱۳

تلفن: ۰۶۱-۳۳۲۷-۷۱
 فکس: ۰۶۱-۳۳۲۷-۸۱۳